


Male Branch Tee: KQ2T



Applicable tubing O.D. (mm)	Connection thread Uni One-touch fittings	Model	H (width across flats)	⁽¹⁾		L1	L2	A*	M	Effective area (mm ²) ⁽²⁾		Mass (g)	
				øD1	øD2					Nylon	Urethane		
4	1/8	KQ2T04-U01	10	10.4	10	18	20	21.5	16	6.0	6.0	9	
	1/4	KQ2T04-U02	14				22					15	
6	1/8	KQ2T06-U01	10	12.8	10	20	21.5	23.5	17	13.9	13.9	11	
	1/4	KQ2T06-U02	14				23					17	
		KQ2T06-U03	17				24					26	
	3/8	KQ2T06-U03	17				24					24.5	26
8	1/8	KQ2T08-U01	12	15.2	12	23	22.5	26	18.5	26.3	18.2	15	
	1/4	KQ2T08-U02	14				24.5					20	
		KQ2T08-U03	17				25.5					28	
	3/8	KQ2T08-U03	17				25.5					27	28
10	1/8	KQ2T10-U01	17	18.5	17	26.5	25	29.5	21	35.2	25	30	
	1/4	KQ2T10-U02	17				26.5					30	27
		KQ2T10-U03	17				27					30.5	31
	1/2	KQ2T10-U04	22				30					31.5	51
12	1/4	KQ2T12-U02	17	20.9	17	28.5	27	31.5	22	57.2	45.2	31	
	3/8	KQ2T12-U03	17				28					32.5	34
		KQ2T12-U04	22				31					33.5	54
	1/2	KQ2T12-U04	22				31					33.5	54
16	3/8	KQ2T16-U03	22	26.5	21	33	33	40.5	24	71	(71)	62	
	1/2	KQ2T16-U04	22				35					40.5	100

* Reference dimensions after Uni thread installation. Note 1) øD1: Max. diameter
 Note 2) Dimensions in () are the case of soft nylon tubing.



- K
- M
- H
- KK
- D
- MS
- LQ
- MQR
- T

Male Run Tee: KQ2Y



Applicable tubing O.D. (mm)	Connection thread Uni One-touch fittings	Model	H (width across flats)	⁽¹⁾		L1	L2	A*	M	Effective area (mm ²) ⁽²⁾		Mass (g)	
				øD1	øD2					Nylon	Urethane		
4	1/8	KQ2Y04-U01	10	10.4	10	18	20	34	16	6.4	6.4	9	
	1/4	KQ2Y04-U02	14				22					34.5	15
6	1/8	KQ2Y06-U01	10	12.8	10	20	21.5	37.5	17	13.4	13.4	11	
	1/4	KQ2Y06-U02	14				23					37	17
		KQ2Y06-U03	17				24					38	26
	3/8	KQ2Y06-U03	17				24					38	26
8	1/8	KQ2Y08-U01	12	15.2	12	23	22.5	41.5	18.5	25.6	17.7	15	
	1/4	KQ2Y08-U02	14				24.5					19	
		KQ2Y08-U03	17				25.5					28	
	3/8	KQ2Y08-U03	17				25.5					42.5	28
10	1/8	KQ2Y10-U01	17	18.5	17	26.5	25	46.5	21	40.0	28.4	30	
	1/4	KQ2Y10-U02	17				26.5					47.5	27
		KQ2Y10-U03	17				27					48	31
	1/2	KQ2Y10-U04	22				30					49	51
12	1/4	KQ2Y12-U02	17	20.9	17	28.5	27	49.5	22	57.4	45.4	31	
	3/8	KQ2Y12-U03	17				28					50.5	35
		KQ2Y12-U04	22				31					51.5	55
	1/2	KQ2Y12-U04	22				31					51.5	55
16	3/8	KQ2Y16-U03	22	26.5	21	33	66	40.5	24	81	(81)	61	
	1/2	KQ2Y16-U04	22				113					(113)	62

* Reference dimensions after Uni thread installation. Note 1) øD1: Max. diameter
 Note 2) Dimensions in () are the case of soft nylon tubing.

