



CONFIGURATION

X	Control	Standard Pilot
Y	Spool Configuration	A and B to T Center
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

Three-position, 4-way directional cartridges are spring-centered, 6-port directional valves that can be configured from a choice of spool options. The supply port is port 3 and all ports will accept 5000 psi (350 bar). Capacity for these pilot-to-shift valves is dependent on the spool type specified.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-62A
Series	2
Capacity	38 - 120 L/min.
Minimum Pilot Pressure Required to Shift Valve	10,5 bar
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min. @70 bar
Pilot Volume Displacement	0,98 cc
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990062007
Seal kit - Cartridge	Polyurethane: 990062002
Seal kit - Cartridge	Viton: 990062006
Model Weight	0.37 kg.

CONFIGURATION OPTIONS

Model Code Example: DCDCXYN

CONTROL	(X)	SPOOL CONFIGURATION	(Y)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Standard Pilot		Y A and B to T Center		N Buna-N		Standard Material/Coating
		A A to T Center		E EPDM		/AP Stainless Steel, Passivated
		B B to T Center		V Viton		/LH Mild Steel, Zinc-Nickel
		C Blocked Center				
		H Open Center				
		N P to A and B to T Center				
		R Regen Center				
		T Tandem Center				
		W A and B Bleed to T Center				

TECHNICAL FEATURES

- All ports will accept 5000 psi (350 bar), including the x and y pilot ports (port 5 and port 6).
- The reason for the different capacities, or performance limits, for the different spool configurations are flow forces. Flow forces are proportional to flow and pressure drop. Typically, they resist the opening of a passage. Spool configurations that open passages as they spring center are the most susceptible. If the flow forces due to the flow and pressure conditions exceed the centering spring force the valve may not shift completely. Higher flows may be used at lower pressures.
- Leakage listed in technical data is for each path.
- The pilot ports, 5 and 6, are positively sealed from the work ports.
- Hardened spool and sleeve provide consistent and low spool leakage rates and excellent wear characteristics.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

